



GAS DUST/ODOR CONTROLLER



GAS DUST/ODOR CONTROLLER

- **OSCILLATION UP TO 270°**
- **POWERFUL & VERSATILE**
- **STANDARD GARDEN HOSE HOOK-UP**



BUFFALO TURBINE



TALK WITH OUR EXPERTS

8AM-4:30PM (Mon-Fri) EST

(716) 592-2700

BuffaloTurbine.com

GASOLINE DUST/ODOR CONTROLLER

TOP BENEFITS

- Powerful and versatile
- Easy to operate and maintain
- Self contained
- Requires only standard water pressure
- 10 Year Manufacturer's Warranty

TOP FEATURES

- High speed oscillation up to 270°
- Non-oscillating option available
- 3 wheel off-road trailer package for ease of transport
- 6 gallon fuel capacity
- Standard garden hose hookup

GENERAL INFO

- Oscillation: 180° (capable of 270° upon request)
- Hand held wireless transmitter (water resistant) with push button control (manual control option available)
- Min/Max water pressure: 40psi - 120psi
- Min/Max water volume: 1/3 gallon - 20 gallons per minute at 120psi
- Throw distance (neutral wind conditions): Vertical-up to 50 ft / Horizontal-up to 125 ft
- Gyrotary atomizing nozzle system
- Outlet size: 12"
- Hose input: 3/4" utility / garden hose
- Droplet size: 50 - 200 microns

ENGINE SPECS

- Engine start/stop function (no choke required)
- ECH749 Kohler Gasoline Engine
- 26.5 HP Fuel Injected Engine
- Adjustable throttle up to 3900 RPM (more fuel economy when ran at 3600 RPM)

PHYSICAL SPECS

- Frame length: 48"
- Overall length w/nozzle: 126" (105" w/handle turned to the side for transporting)
- Length w/out wheels and handle: 76"
- Max width: 48" (34" w/wheels and handle removed)
- Max height w/nozzle in upright position: 58"
- Weight: 800 lbs.

Applications

Demolition Sites • Landfills • Wood Recycling
Scrap Metal Recycling • Aggregate Processing
Waste Transfer • Indoor Recycling Facilities

OPTIONS



Lifting Bracket



Fork Lift Pockets



Aerospace Polymer Nozzle



300 Gallon Tank

