



ELECTRIC DUST/ODOR CONTROLLER



ELECTRIC DUST/ODOR CONTROLLER

- 3 PHASE
- HIGH SPEED OSCILLATION UP TO 270°
- INDOOR/OUTDOOR USE
- DECREASED EMISSIONS



TALK WITH OUR EXPERTS
8AM-4:30PM (Mon-Fri) EST
(716) 592-2700
BuffaloTurbine.com

ELECTRIC DUST/ODOR CONTROLLER

TOP BENEFITS

- Reduce operating cost
- Decreased emissions
- Save on water consumption compared to other methods
- Very minimal maintenance
- Only requires standard water pressure (30-120 psi)
- Indoor/Outdoor use
- 10 year manufacturer warranty

TOP FEATURES

- High speed oscillation up to 270°
- Able to permanently fix mount
- Great for both indoor and outdoor applications
- No nozzle tips (atomizing nozzle) = no clogging
- 3/4" garden hose inlet
- NEMA 4 rated control box

MOTOR SPECS

- 3 phase
- Available in 220V, 330V, 460V, 575V
- 20 HP electric motor
- Variable speed up to 3550 RPM
- 1 year motor warranty



Atomizing Nozzle - No Clogs

Applications

Demolition Sites • Landfills • Wood Recycling
Scrap Metal Recycling • Aggregate Processing
Waste Transfer • Indoor Recycling Facilities



WARNING: Cancer & Reproductive Harm - www.P65Warnings.ca.gov

